




THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.

DWN No.: C-20101011307



proposal



Recommended Dimensions of HSG

DIST

DIST

3	CHANGE Normal Force	2016/01/11
2	CHANGE PLATING SPEC	2015/12/21
1	NEW	2015/12/16
Rev.	Revision record.	Date.

Top-Link
Electronics Ltd.
TOLERANCES UNLESS
OTHER SPECIFIED
0. = ±
0.0 = ±0.15
0.00 = ±0.10
0.000 = ±
Angle: ±
SURF TEXTURE:
REMOVE BURRS.
BREAK SHARP EDGES
R0.05 MAX.DO NOT
SCALE PRINT.

Type	Customer drawing	Unit	mm	Weight	
DWN:	Eric	APVD:		<i>top-Link</i> Electronics	Top-Link Electronics Ltd.
CHK:		REL:			
Name Pogo pin connector					
Scale	Size	DWG No.	C-20101011307	Page	Rev.
1:1	A4			1/1	3

Item	Part name	Q'ty/Ea'	Material	Finish
1	Body	1	Leaded Brass	Pd-Ni Au0.75um plating over Nickel plating
2	Plunger	1	Leaded Brass	Au0.40um plating over Nickel plating
3	Spring	1	Stainless steel wire	

Table 1 Mechanical performance

working height	3.90mm	30 ⁺¹⁵ ₋₅ gf <2.1>	△
Durability	10000cycle		

TOP-LINK

Notes:

- Dimensions shall be interpreted per ASME Y14.5M.
- Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
<2.2>Warning: Working height are not permitted to be less than Min working height.
- Electrical performance
Resistance: 30mOhm Max.
Current rating: 1.0A
- RoHS compliant.

20101011307

PART NUMBER

A