






Recommended PCB Layout

- Notes:
- 1 Material, Housing: PA 4,6 (30% Glass Filled)
Color: Black
Contact: Brass
 - 2 Mechanical demands:
Plating Plunger: Min 0.4um Au over 14um Ni
Plating Body: Min 0.1um Au over 14um Ni.
 - 3 Electrical
a) Contact resistance: 30mOhm Max.
b) Current rating: 2.0A
c) Operating voltage: 36VDC
d) Force: 150±30gf per pin at 1.00mm stroke

LDC
-
DIST
-

NEW			2012/05/25
REVISION			
RECORD			
APVD			
DATE			

DIMENSIONS IN MM
TOLERANCES UNLESS
OTHER SPECIFIED
0 = ±
0.0 = ±0.15
0.00 = ±0.10
0.000 = ±
ANGLE: ±1°
SURF TEXTURE: 32/
REMOVE BURRS, BREAK
SHARP EDGES R0.05 MAX
DO NOT SCALE PRINT

MATL	HT TR	FIN	NAME	SCALE	A4	DWG NO.	PGGD 3P	SHEET	REV
1	—	—	PGGD 3P	1:1	A4	C-100418	PGC-1.5-5.0-R-3P-3.0PH	1 OF 1	B
DWN	APVD		Top-Link Electronics Ltd.						
CHK	REL								

100418-3

PART NUMBER

Top-Link Electronics Ltd.

USED ON

-