




proposal



Notes:

- 1 Demensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- <2.2>Warning: Working height are not permitted to be less than Min working height.
- 3 Electrical performance
- Resistance: 50mOhm Max.Current rating: 2.0A
- 4 Packaging Spec.Comformance to EIA 481
- 5 RoHS compliant.

TOP-LINK



Item	Part name	Q'ty/Ed	Material	Finish
1	HSG	1	High temp.Plastic UL94 V-0 Color Black	_____
2	Body	3	Leaded Brass	Gold plating over Nickel plating
3	Plunger	3	Leaded Brass	Gold plating over Nickel plating
4	Spring	3	Stainless steel wire	_____
5	CAP	1	High temp.Plastic UL94 V-0 Color Black	_____

Table 1 Mechanical performance

Working height	4.50mm	75±25gf <2.1>
Durability	10000cycle	

DIST

Rev.	NEW	2011/12/28
Revision record.		Date.

Top-Link Electronics Ltd.	Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED	DWN:	Qin Zuozhong	APVD:		
0.0 = ±0.15	CHK:		REL:		
0.00 = ±0.10	Name	Customer drawing			
0.000 = ±0.05	Scale	1:1	Size	A4	DWG No.
Angle: ±1°					C-100774
SURF. TEXTURE:					Page 1/1
REMOVE BURRS:					Rev. 1
BREAK SHARP EDGES					
RO.05 MAX.DO NOT					
SCALE PRINT.					

Top-Link
Electronics
Electronics Ltd.

100774-3
PART NUMBER