



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWN No.:

C-10101031148

proposal



TOP-LINK

Notes:

- Dimensions shall be interpreted per ASME Y14.5M.
- Mechanical performance(See the table 1)
 - <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
 - <2.2>Warning: Working height are not permitted to be less than Min working height.
- Electrical performance
 - Resistance: 30mOhm Max.
 - Current rating: 2.0A
- Packaging specification conforms to EIA 481
- RoHS compliant.

Item	Part name	Qty/Ed	Material	Finish
1	HSG	1	High temp.Plastic UL94 V-0 Color Black	_____
2	Body	3	Leaded Brass	Gold plating over Nickel plating
3	Plunger	3	Leaded Brass	Gold plating over Nickel plating
4	Spring	3	Stainless steel wire	_____
5	CAP	1	High temp.Plastic UL94 V-0 Color Black	_____

Table 1 Mechanical performance		
working height	5.50mm	90gf min <2.1>
Durability	10000cycle	

DIST

2	change tolerance	2014/06/03
1	NEW	2014/03/24
Rev.	Revision record.	Date.

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Gui zhiguo	APVD:			
0.0 = ± 0.15		CHK:		REL:		<i>Top-Link Electronics</i>	Top-Link Electronics Ltd
0.00 = ± 0.10							
0.000 = ± 0.05							
Angle: ±1°							
SURF TEXTURE:							
REMOVE BURRS.							
BREAK SHARP EDGES							
R0.05 MAXDO NOT SCALE PRINT.							
Name		Pogo pin connector					
Scale	Size	DWG No.					
1:1	A4	C-10101031148					
			Page	1/1		Rev.	2