

DWG NO.
C-101086

TOP-LINK

- Notes:
- Material:
 - 1)Puncher & Body : CuZn36 Pb3, H02 (C36000) or CuZn39 PB3 or CuZn38 PB2.
 - 2)Spring : Stainless steel wire
- 2 Plating
 - 1)Body: Gold plating over Nickle plating
 - 2)Puncher: Gold plating over Nickle plating
- 3 Mechanical
 - 1)Total stroke : 0.75mm
 - 2)Durability: 10,000 cycle min.
- 4 Electrical
 - 1)Contact resistance: 30mOhm Max.
 - 2)Operating voltage: 36VDC

USED ON

	NEW		2007/08/01
LTR	REVISION RECORD	APVD	DATE

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED				MATL		HT TR	—	FIN	— 
0	= ±	—	DWN	APVD	 Top-Link Electronics Ltd.				
0.0	= ±0.10	—	Benny	Lansing					
0.00	= ±	—	CHK	REL					
0.000	= ±	—	Andy						
ANGLE: ±1°			NAME		POGO PIN				
SURF TEXTURE: 32/					PG-1.0-1.0-2.0-0.4-1.5-2.6-3.4				
REMOVE BURRS, BREAK SHARP EDGES TO .05 MAX			SCALE	A4	DWG NO.	C-101086		SHEET 1 OF 1	REV A
DO NOT SCALE PRINT			1:1						

101086-1
PART NUMBER