






THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWG NO.
C-110686



Recommended PCB Layout



TOP-LINK

Notes:

1 Material, Housing: PA 4.6 (30% Glass Filled)

Color Black.

Contact: Brass

2 Mechanical demands:

1)Plating Plunger: 0.4um Au over 1.4um Ni

2)Plating Body: 0.1um Au over 1.4um Ni.

3 Mechanic:

1)Total stroke : 1.40mm

2)Durability: 10,000 cycle min.

4 Electrical

1)Contact resistance: 30mOhm Max.

2)Voltage rating: 36V DC Max

3)Current rating: 2.0A

USED ON

-

110686-3

PART NUMBER

MATL	HT	TR	FIN
	—	—	

DWN	APVD
Qin	
CHK	REL

Top-Link
Electronics L td.

NAME
PGGD 3P
PGC-1.5-5.5-R-3P-3.0PH

SCALE	A4	DWG	NO.	C-110686	SHEET	REV
1:1					1 OF 1	1

LDC

-

DIST

-

4

3

2

1